

IDEAL 5009

Simply gigantic: for really large quantities and complete lever arch files

Large feeding table with conveyor belt and electronically secured safety guard in the feeding area. Control panel for forward/stop/reverse. Safety lock and key, main switch and emergency cut-off switch. Optical indicators for the operational status. 2-MATIC – two automatic speed levels with automatic adaption of the shred speed to the paper quantity fed. Electronic control prevents overfeeding: automatic reverse and refeeding in case of paper jams. Automatic cut-off if the shred bag is full. Centralised oiler for convenient lubrication of the shredding head. Large shred compartment with electronically secured door on the rear side of the machine. Shred trolley with plastic bag mounting frame and 300 litres capacity. Powerful three phase motors (9.0 kW). Thermal motor protection. Robust shredding heads with special hardened cutting shafts made of high-quality steel, resistant against soft metal objects. Machine mobile on castors. Accessories at an extra cost: second shred trolley and a modular conveyor belt system for the shred exit area. Two years guarantee on the cutting tools, one year on all other parts. Power connection (other voltages available): 400 V / 50 Hz / 3~ (three phase). Dimensions (H x W x D): 1714 x 1036 x 2170 mm; Depth with modular conveyor belt system: 3070 mm; Weight: 1130 kg.

Optional accessory for IDEAL 5009-2 CC and IDEAL 5009-3 CC

Offers flexibility for individual shred disposal needs. Easy and secure mounting – the modular conveyor belt system is placed into the shred exit area and locked. Electric belt drive (100 Watt motor), controlled by the shredder electronics. Electrically secured locking system. Mobile on castors.

Dimensions (H x W x D): 1160 x 690 x 1900 mm, Weight: 99 kg.

SHREDDER TYPE 5009-2 CC

8 x 40-80 mm cross cut

Sheet capacity*: 600-700 / 500-600

Security level 2

SHREDDER TYPE 5009-3 CC

6 x 50 mm cross cut

Sheet capacity*: 300-400 / 250-350

Security level 3

* A4 paper, 70 g/m² / 80 g/m²



IDEAL 5009

Features



ROBUST SHREDDING HEADS Complete lever arch files including metal components can be shredded due to the high-quality, tempered steel cutters.



EASY LUBRICATION A centralised oiler for easy lubrication of the cutting head is standard equipment on this high-capacity shredder.



SHRED TROLLEY The door on the rear side of the shredder is electronically secured and allows safe and easy removal of the shred trolley.



CONVEYOR BELT SYSTEM By using the conveyor belt system the output of the shredder can be doubled (removing of the full plastic bag is not necessary).

