

16 Programmable Channels Built-in CTCSS/DCS Wide/Narrow Band Selectable Time out Timer Voice Prompt Function







Super Bright Flashlight

Standby time 120 hours
Super Low Radiation



MT-R3

16 Programmable Channels Built-in CTCSS/DCS Wide/Narrow Band Selectable Time out Timer Voice Prompt Function



Standby time 120 hours
Super Low Radiation



SPECIFICATION

GENERAL		TRANSMIT PART	
Frequency Range	UHF: 400~480MHz	RF Power	3W
Operating Temperature	-20°C~+60°C	Modulate Mode (W/N)	16KΦF3E,11KΦ
Frequency Combination	Phase lock frequency synthesize	Max. Freq. Deviation (W/N)	<5K / <2.5KHz
Frequency Stability	±2.5ppm	Remain Wave Radiation	<-60dB
Memory Channel	16 Channels	Transmitting Current	≤1300mA
Working voltage	DC 3.7V	RECEIVE PART	
Antenna Impedance	50Ω	Sensitivity	<0.25µV(12dB \$
Operating Mode	Simplex of co-frequency or alien	Squelch Sensitivity	<0.20µV
	frequency	Intermodulation Antijamming	50dB
Dimension	97mm×57mm×30mm	Audio Power output	500mW
Weight	200g (Include Battery Pack)	Receiving Current	≤100mA
		Squelch Standby	20mA

Notice: Saving your presence, no additional notice will be sent if specification changes because of technology-improving.