

BNV325 VIRTUE SERIES

NETWORK VIDEO RECORDER

compatible with:

≰ iPhone *** BlackBerry. I ¶ an⊃∃ol⊃



KEY FEATURES

- 24ch 5M/ 32ch 4M/ 16ch 1080P video input
- VGA, HDMI simultaneous video output
- H.265/H.264
- 1*10/100Mbps Ethernet port, RJ45 port
- DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP search, Alarm center
- Support the Onvif protocol
- Cloud services, P2P, Smartphone Notification
- Support remote access & ARSP
- Triple watchdog function
- Support WEB, CMS, VMS, MYEYE Platform
- 4 SATA (Up to 8TB)















HD Local Display findNVR for

Compatible with CMS

Multi-Platform Mobile Client







Pan Tilt Zoom

FEATURE IMAGES

H.265 VIDEO FORMAT



Compared with H. 264, the greatest strength of H. 265 is that it has a higher compression ratio, which can be discerned from its name. H.265 is also called HEVC (High Efficiency Video Coding), and the primary use is to further reduce the design flow rate, in order to lower the cost of storage and transmission.

At the same quality of coding, H. 265 can save around 50% of the bit rate, and coding efficiency can be doubled than H. 264. As H.265 provides more different tools to reduce the bit rate.

H.265 Bandwidth Consumption Same quality of video data, the H.265 can save 70~80% bandwidth sources.

TECHNICAL SPECIFICATIONS

Video Input 24ch 5M/ 32ch 4M/ 16ch 1080P Playback 4ch 5M/ 9ch 4M/ 16ch 1080P

Decode H.265/H.264 Compression G.711a Intercom Support

Record Mode Manual> Alarm> Motion detection> Timing Inquire Mode Inquire by Time/Calendar/Event/Channel Storage Mode HDD Storage, Network Storage

Backup Network, USB, SATA **HDMI** Output 1*HDMI (MAX:4K) VGA Output 1*VGA (MAX:1080P)

Ethernet Port 1*RJ45 1*10/100Mbps Ethernet port

POE Port N/A Audio I/O 1/1 Alarm I/0 16/4

USB Port 2*USB2.0 ports, 1*USB3.0 ports HDD 4*SATA interface (Up to 8TB)

Temperature 0°C ~ 55°C Humidity 10% -90% RH **Power Supply** 12V/6A

Power Consumption <10W (Without HDD)

Weight 2.6KG

Dimension 440L)* 400.5mm(W)* 60mm(H)