

# IPD65

LITE SERIES

IR NETWORK DOME CAMERA



## KEY FEATURES

- 1/3" 4.0MP progressive scan CMOS
- Indoor application
- Support 2592\*1520 high definition image
- Support multiple stream resolution
- Varifocal 2.8mm-12mm lens
- Support ONVIF protocol interface
- 36 IR LEDs
- 30m IR range
- H.265 Video Compression format
- Min illumination 0lux (IR LED)
- P2P cloud service
- IR-CUT optical filter technology



Day & Nite



Infra Red



4 MEGAPIXEL

## TECHNICAL SPECIFICATIONS

Image Sensor	1/3" 4.0MP progressive scan CMOS
Resolution	4MP
Min. Illumination	0.01Lux @(F1.2,AGC ON), 0Lux with IR
IR Distance	30m
Shutter	Manual /Auto (Adjustable, 1/25~1/100000)
Lens	Varifocal 2.8mm-12mm, M12 mount
Day & Night	Auto (ICR) / Color / Black & White
Video Compression	H.265
Video Output Bitrate	128Kbps~8Mbps
Audio Compression	G.711
Max. Resolution	Main stream: 2592*1520, sub stream: 720*576
Protocols	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,PPoE,NTP,UPnP,SMTP,SNMP,IGMP,802.1X,QoS,IPv6
Interface Protocol	ONVIF /Private CGI
General Function	Flicker Filter, Dual-stream, Mirror Image
Communication Interface	RJ45 ( 10M/100M Ethernet)
Working Temperature	-30°C~50°C
Power Supply	DC12V/POE
Power Consumption	15W
Rating	IP67, IK8

## IMAGE SETTING

WDR	Digital WDR
Day & Night	Auto/Black&White/Color
Noise Reduction	Auto/manual
Exposure Mode	Auto/manual
Flip	Horizontal/Vertical