

This series is specially designed with the highest degree of protection against most sophisticated tools and techniques used in burglary today. It provides maximum protection for your valuables, important documents and especially cash from burglary and fire.

Body

: The main frame is constructed with an overall thickness measuring 102mm (4ins) reinforced with high density proofing material encased in steel. The body provides strong resistant from penetration attempt with oxyacetylene torch of high tech mechanical tools.

Door


: Full length vertical interlocking rebate encrusted with 160mm (6.3ins) thickness of high density fire proofing materials and a 60mm (2.4ins) thickness door slab secures lock tight position in the even of break-in attempt using hydraulic jack, explosive or sawing of the door hinges.

Locking


: A 3-way moving rod 32mm (1.25ins) for the front, upper and lower section of the door. A 1,000,000 combination threee-wheel locking system and additional high security 7-lever key.

APS Safe Incorporate full length reinforced vertical interlocking rebate securing the back ensuring the door remain locked in the even of hydraulic jack attack, explosive attack or the hinges are swanked off.













Model	Dimension (H x W x D) mm		Net Weight
	external	internal	+/- kg +/- lbs
BK 1	712 x 610 x 660	512 x 378 x 416	500 1100
BK 2	890 x 686 x 737	690 x 457 x 485	720 1584
BK 3	1092 x 762 x 870	893 x 533 x 643	990 2178
BK 4	1386 x 762 x 870	1187 x 533 x 643	1180 2596
BK 5	1651 x 762 x 870	1452 x 533 x 643	1380 3036
BK 6	1825 x 762 x 870	1630 x 533 x 643	1590 3498



Authorized Dealer

www.aps-safe.com enquiry.my@aps-safe.com