



80mm Thermal Receipt Printer TP-3250D

- ◆ Low Noise thermal printing with 250mm/sec speed
- ◆ Built in data buffer
- ◆ Receipt printout alerting and error alarm function
- ◆ Printer authentication and software bundle
- ◆ Support various international fonts
- ◆ Parallel + USB or serial + USB port
- ◆ Support cash drawer connection
- ◆ OPOS and Linux driver
- ◆ Windows 9X,ME,2000,2003,NT,XP,Vista and 7 compatible with EPSON, SAMSUNG



Model	TP-3250D
Print method	Line Thermal line
Printing width	64mm / 512 dots
Dot pitch	576 dots / line & 512 dots / line (60 line per sec)
Printing speed	250mm / sec
Number of Columns	80mm : Font A – 42 columns / 48 columns Font B – 56 columns / 64 columns / Simplified / Traditional Chinese – 21 columns / 24 columns
Character Size	ANK Character Font A: 1.5 x 0.3mm (12 x 24 dots) Font B: 1.1 x 2.1mm (9 x 17 dots) Simplified / Traditional Chinese :
Character table	PC437 / Katakana / PC850 / PC860 / PC863 / PC865 WPC 1252 / PC866 / PC852c / PC858 / Latvian / Arabic / PT151 , 1251
Barcode Type	UPC-A/UPC-E/JAN-13/EAN-8/CODE39/CODE93/CODE128
Line spacing	3.75mm
Paper	79.5 +/- 0.5mm @ 83mm
Interface	RS232 + USB or USB + LPT
Input buffer	128K bytes
NV user memory	256K bytes
Drawer Kick-Out	DC-12-24V /1A, 2 Drawer
Power Supply	DC 24V/2.5A
AC adapter	Input : AC 110V / 220V , 50-60 Hz Output : DC 24V / 2.5A
Weight	1.60kg
Operating	Temperature : 0° – 45° C , Humidity: 10 – 80 % Temperature : 0° – 60° C , Humidity: 10 – 90 %
Reliability	100KM
Driver	Win9x / WinXP / Win NT / Win2K / Win Vista
Compatible	ESC / POS
Dimension	137 x 197 x 144mm
Safety	3C , CE

All specifications are subject to change without notice

All Company and / or product names are trademarks and / or registered trademarks of their respective owners