
HSM Document Shredders

Data protection for all application areas





 Available in • max. 7 sheets per cycle **HSM 70.2** security level 2 Container volume 14 l Intelligent basic model for work at home · Available in max. 12 sheets per cycle **HSM 80.2** Container volume 17 I Compact universal shredder Available in max. 15 sheets per cycle HSM 90.2 security levels 2 Container volume 25 l Perfect size for small offices and 3 Available in • max. 18 sheets per cycle **HSM 102.2** security levels 2 Container volume 25 l Convenience with an attractive design and 3

Versatile document shredders, used ideally under the desk or as central devices for larges offices.

Highly efficient at the desk - also suitable for shredding credit and store cards and CDs

Multi-functional compact model - also shreds credit and store

Ideal for busy offices - also shreds credit and store cards and

CDs

Professional data security model for larger offices – also shreds credit and store cards, CDs and floppy disks

Perfect central device for large offices – also shreds credit and store cards, CDs and floppy disks



Powerfull shredders for entire IT departments or office floors. Entry-level model in the PROFESSIONAL class - also shreds credit and store cards and entire computer lists

Professional model for large offices or entire office floors also shreds credit and store cards, CDs and floppy disks

Security expert meets all demands and for the frequent shredding of crumpled paper - also shreds credit and store cards, CDs, floppy disks and DAT cartridges

Power-pack can process even very large quantities - also shreds credit and store cards, CDs, floppy disks, entire computer lists and crumpled paper



· max. 25 sheets per cycle

Container volume 116 l



 max. 67 sheets per cycle Container volume 146 l Intake width 400 mm 	 Available in security levels 2, 3, 4 and HS level 6 (412.2 in level 3 only) 	HSM 411.2/412.2
 max. 85 sheets per cycle Container volume 290 l Intake width 443 mm 	 Available in security levels 3 and 4 	HSM 450.2

Available in

security levels 2,

High-volume models with extremely high output for large IT departments and archives or as a central shredding point.

Mobile top models, specialised on continuous operations at large departments and archives or as central shredding points - also shreds credit and store cards, CDs and floppy disks




 max. 180 sheets per cycle Container volume 460 I Intake width 428 mm 	 Available in security levels 1, 2 and 3 	HSM FA 400.2
 max. 440 sheets per cycle Intake width 500 mm Collection trolley optional 	 Available in security levels 1, 2 and 3 	HSM FA 490.1
 max. 650 sheets per cycle Intake width 500 mm Collection trolley optional 	 Available in security levels 2 and 3 	HSM FA 500.2

"Made in Germany" – for highest demands



HS Level 6: The security level HS Level 6, developed by HSM, is an example of the particular efficiency of our document shredders. This highest security level was originally developed specially for top international state security authorities.



The V groove of the cutting rollers is another development by HSM in terms of shredding equipment: The new, extremely efficient and high-precision cutting mechanism of the V GROOVE enables a considerably higher cutting capacity at the same energy input.

It's what's inside that counts. As with a top-class modern computer, the inner qualities of document shredders can only be guessed at from the outside. Whether specially hardened solid steel cutting rollers or thermally protected quality motors - with all of its sophisticated inner technological developments, HSM is one of the leading document shredder manufacturers.



For general documents that are to be rendered illegible after expiry



For confidential documents such as personal data and documents



SECURITY LEVEL 5

For secret documents where extraordinary security requirements must be adhered to, such as government offices or fundamental research



SECURITY LEVEL 2

For internal documents that need to be rendered illegible such as computer lists or bad copies



SECURITY LEVEL 4

When the confidentiality of documents is of existence importance for the company



HS Level 6

This is the maximum security feature developed by HSM (out of DIN standard) – especially for shredding highly confidential documents





HSM 70.2 COMPACT

max. 7 sheets

The intelligent basic model for work at home.

- This document shredder can also be used as a waste paper basket for non-confidential material thanks to its infeed opening
- Intake width: 225 mm
- Machine height: 384 mm
- Container volume: 14 litres
- Available in the following cutting versions:
 5.8 mm strips, security level 2,
 max. 7 sheets per cycle
 3.9 mm strips, security level 2,
 max. 5 sheets per cycle

HSM 80.2 COMPACT

max. 12 sheets

The compact universal shredder.

- Intake width: 225 mm
- Machine height: 410 mm
- Container volume: 17 litres
- Cutting roller with HSM V groove for particle cut model
- Available in the following cutting versions:
 5.8 mm strips, security level 2,
 max. 12 sheets per cycle
 3.9 mm strips, security level 2,
 max. 8 sheets per cycle

4 x 25 mm particles, security level 3,

max. 5 sheets per cycle



Top part which can be easily



Container is also used as a waste paper basket



Automatic start/stop control



Rocker switch for on/off and



Powerful drive, thermally protected motor













HSM 90.2 COMPACT

max. 15 sheets

The perfect size for small offices.

- This document shredder can also be used as a waste paper basket for non-confidential material thanks to its infeed opening (strip cut versions)
- Also suitable for shredding credit cards and store cards (security level 2)
- Cutting roller with HSM V groove for particle cut model
- Intake width: 225 mm
- Machine height: 423 mm
- Container volume: 25 litres
- Available in the following cutting versions: 5.8 mm strips, security level 2, max. 15 sheets per cycle 3.9 mm strips, security level 2, max. 12 sheets per cycle 4 x 25 mm particles, security level 3, max. 6 sheets per cycle



HSM 102.2 COMPACT max. 18 sheets

Convenience with an attractive design.

- Most powerful document shredder of the COMPACT class with integrated container for easy removal of the shredded material
- Filling level display through integrated inspection window in container
- Auto-stop when container is full
- Also suitable for shredding credit cards and store cards (security level 2)
- Closed housing provides protection against paper dust
- Cutting roller with HSM V groove for particle cut model
- Intake width: 225 mm
- Machine height: 500 mm
- Container volume: 25 litres
- Available in the following cutting versions: 5.8 mm strips, security level 2,

max. 18 sheets per cycle

3.9 mm strips, security level 2,

max. 15 sheets per cycle

1.9 mm strips, security level 3,

max. 9 sheets per cycle

4 x 25 mm particles, security level 3,

max. 7 sheets per cycle

HSM 102.2 COMPACT Up to 15 sheets

silver edition

details see HSM 102.2 COMPACT

- Available in the following cutting versions: 3,9 mm strips, security level 2,
 - max. 15 sheets per cycle
 - 4 x 25 mm particles, security level 3,
 - max. 7 sheets per cycle



removed (HSM 90.2)



Container is also used as a waste paper basket



Automatic start/stop control



Rocker switch for on/off and















HSM OFFICE

At the various security levels in accordance with DIN 32757-1 and HSM's own level, HS Level 6, the devices of the HSM OFFICE series are designed specifically for use at the desk or as central devices for large offices. Ideally technically equipped, our OFFICE models ensure a permanent high capacity. The large OFFICE machines not only shred paper, but also CDs.

HSM OFFICE – The technical features:

- Designed specially for continuous operation
- Hardened solid steel cutting rollers, unaffected by staples and paper clips
- Powerful drive for high performance even when used for long periods of time – thermally protected motor
- Tried-and-tested closed gear box prevents dirt and wear, thus increasing the service life
- Closed housing provides protection against paper dust
- Rocker switch for on/off and reverse
- Cutting rollers with HSM V groove
- Automatic control via photoelectric cell (from HSM 105.3)



HSM 104.3 OFFICE

max. 24 sheets

Highly efficient at the desk, also suitable for shredding credit and store cards.

- Automatic start/stop control with rocker switch
- Stand-by operation without power consumption
- Auto-stop when container is full or has been removed
- Also shreds credit and store cards and CDs (5.8 mm strips)
- Integrated container which can be tilted out and used as a waste paper basket for non-confidential documents
- Filling level display through integrated inspection window in container
- Runs quietly
- Intake width: 240 mm
- Machine height: 583 mm
- Container volume: 33 litres
- Available in the following cutting versions:

5.8 mm strips, security level 2,

max. 24 sheets per cycle

3.9 mm strips, security level 2,

max. 18 sheets per cycle

1.9 mm strips, security level 3,

max. 14 sheets per cycle

3.9 x 30 mm particles, security level 3,

max. 14 sheets per cycle

1.9 x 15 mm particles, security level 4,

max. 11 sheets per cycle

HSM 105.3 OFFICE

max. 24 sheets This multi-functional compact

model also shreds credit and store cards with ease.

- electronical, automatic start/stop control, especially convenient via photoelectric cell
- LED indicating readiness for operation
- LED indicating full paper basket
- Auto-stop when container is full or has been removed
- Also shreds credit and store cards (security levels 2, 3, 4) and CDs (5.8 mm strips)
- Integrated container which can be tilted out and used as a waste paper basket for non-confidential documents
- Filling level display through integrated inspection window in container
- Runs quietly
- Intake width: 240 mm
- Machine height: 583 mm
- Container volume: 33 litres
- Available in the following cutting versions:

5.8 mm strips, security level 2,

max. 24 sheets per cycle

3,9 mm strips, security level 2,

max. 18 sheets per cycle

1.9 mm strips, security level 3,

max. 14 sheets per cycle

3.9 x 30 mm particles, security level 3,

max. 14 sheets per cycle

1.9 x 15 mm particles, security level 4,

max. 11 sheets per cycle

0.78 x 11 mm particles, security level 5,

max. 6 sheets per cycle





Container is easy to empty



waste paper basket



Powerful drive, thermally pro-



Use of high-quality electronic components (105.3)



Automatic start/stop via light barrier (105.3)





HSM 108.2 OFFICE

max. 24 sheets

With its powerful motor, the HSM 108.2 is ideal for busy offices. It even shreds credit and store cards.

- Automatic start/stop control, especially convenient via photoelectric cell
- · Stand-by operation with LED
- Auto-stop when container is full or door is open
- · Convenient pull-out system with an integrated, sturdy reusable waste bag
- Quiet operation and low-noise running
- Modern electronic control
- Mobile
- Intake width: 240 mm
- Machine height: 727 mm
- Container volume: 48 litres
- Available in the following cutting versions: 5.8 mm strips, security level 2, max. 24 sheets per cycle 3.9 mm strips, security level 2,
 - max. 18 sheets per cycle
- max. 14 sheets per cycle
- 1.9 x 15 mm particles, security level 4,

3.9 x 30 mm particles, security level 3,

max. 11 sheets per cycle

HSM 125.2 OFFICE

max. 30 sheets

This professional data security model is the perfect central device for larger offices. Besides credit and store cards it also shreds CDs with ease.

- Automatic start/stop control, especially convenient via photoelectric cell
- Stand-by operation with LED
- Auto-stop when container is full or door is open
- · Convenient pull-out system with integrated, sturdy reusable waste bag
- Quiet operation and low-noise running
- Modern electronic control
- With infeed slot for floppy disks/CDs (CDs 3.9 and 5.8 mm strips, floppy disks 5.8 mm strips)
- Auto-reverse at security level 5 and HS Level 6
- Mobile
- Intake width: 255 mm
- Machine height: 828 mm
- Container volume: 76 litres
- Available in the following cutting versions:
 - 5.8 mm strips, security level 2,
 - max. 30 sheets per cycle
 - 3.9 mm strips, security level 2,
 - max. 25 sheets per cycle
 - 1.9 mm strips, security level 3,
 - max. 19 sheets per cycle
 - 3.9 x 30 mm particles, security level 3,
 - max. 18 sheets per cycle
 - 1.9 x 15 mm particles, security level 4,
 - max. 14 sheets per cycle
 - 0.78 x 11 mm particles, security level 5,
 - max. 8 sheets per cycle
 - 1 x 5 mm particles, HS Level 6,
 - max. 5 sheets per cycle








Resulting shreds are absolutely



Closed gear box to prevent



Use of high-quality electronic



Automatic start / stop via light























HSM 225.2 OFFICE

The most powerful model of the OFFICE series is a perfect central device for large offices that can also shred credit and store cards without any difficulty. Depending on the cutting version, it also shreds CDs and floppy disks.

- Automatic start/stop control, especially convenient via photoelectric cell
- Stand-by operation with LED
- Auto-stop when container is full or door is open
- Auto stop with LED plus auto reverse for paper jams
- Convenient pull-out system with integrated reusable waste bag
- Quiet operation and low-noise running
- Modern electronic control
- Folding safety element
- With infeed slot for floppy disks and CDs (3.9 and 5.8 mm strips and 3.9 x 40 mm particles)
- Splinter protection for particle cut devices
- Motor and drive designed for continuous operation
- Mobile
- Intake width: 300 mm
- Machine height: 895 mm (especially convenient to use)
- Container volume: 105 litres
- Available in the following cutting versions: 5.8 mm strips, security level 2, max. 42 sheets per cycle 3.9 mm strips, security level 2, max. 33 sheets per cycle 3.9 x 40 mm particles, security level 3, max. 27 sheets per cycle 1.9 x 15 mm particles, security level 4, max. 19 sheets per cycle 0.78 x 11 mm particles, security level 5, max. 11 sheets per cycle 1 x 5 mm particles, HS Level 6, max. 8 sheets per cycle



Integrated, sturdy reusable









CDs are also shredded into



Powerful drive for high cutting



Automatic start / stop via light

























HSM 386.2 PROFESSIONAL max. 25 sheets

The entry-level model in the **PROFESSIONAL** class is excellent value for money. It can process entire computer lists and credit and store cards.

- Auto-stop when waste bag is full or door is open
- Practical storage space for paper stacks
- Computer list unit as a practical accessory

Convenient pull-out system with integrated

- Rocker switch for on/off and reverse
- reusable waste bag
- Also shreds credit and store cards (security levels 2, 3)
- Tried-and-tested closed gear box prevents dirt and wear, thus increasing the service life
- Closed housing provides protection against paper dust
- · Motor and drive designed for continuous operation
- Intake width: 386 mm
- Machine height: 860 mm
- Container volume: 116 litres
- Available in the following cutting versions: 3.9 mm strips, security level 2,

 - max. 25 sheets per cycle
 - 3.9 x 30 mm particles, security level 3,
 - max. 18 sheets per cycle
 - 1.9 x 15 mm particles, security level 4,
 - max. 14 sheets per cycle

HSM 390.3 PROFESSIONAL

This professional model has a high capacity and a large waste volume. It is suited ideally for large offices or entire office floors.



- · Auto-stop with LED and automatic reverse for paper jams
- Rocker switch for on/off and reverse
- Convenient pull-out system with integrated reusable waste bag
- Also shreds CDs, credit and store cards (security levels 2, 3, 4) and even floppy disks (security levels 2, 3)
- Tried-and-tested closed gear box prevents dirt and wear, thus increasing the service life
- · With infeed slot for floppy disks and CDs (3.9 and 5.8 mm strips and 3.9 x 40 mm
- Splinter protection for particle cut devices
- Motor and drive designed for continuous operation
- Intake width: 400 mm
- Machine height: 915 mm
- Container volume: 148 litres
- Available in the following cutting versions:
 - 5.8 mm strips, security level 2,
 - max. 42 sheets per cycle
 - 3.9 mm strips, security level 2,
 - max. 33 sheets per cycle
 - 3.9 x 40 mm particles, security level 3,
 - max. 27 sheets per cycle
 - 1.9 x 15 mm particles, security level 4,
 - max. 19 sheets per cycle
 - 0.78 x 11 mm particles, security level 5,
 - max. 11 sheets per cycle
 - 1 x 5 mm particles, HS Level 6,
 - max. 8 sheets per cycle






Reusable waste bag with pull-





Powerful drive for high cutting capacity



Automatic start / stop via light

















HSM 411.2 PROFESSIONAL max. 67 sheets

At the maximum security level, HS Level 6, this security expert meets all demands. Furthermore it also shreds CDs, credit and store cards as well as floppy disks.

- Touch-sensitive keypad for continuous and reverse operation
- Auto-stop when waste bag is full or door is open
- Automatic reverse for paper jams
- Convenient pull-out system with integrated reusable waste bag
- · Also shreds credit and store cards as well as floppy disks (security levels 2, 3) and CDs (security levels 2, 3, 4) and DAT cartridges (security level 3)
- Folding safety element*
- With infeed slot for floppy disks, CDs and DAT cartridges*
- Splinter protection for particle cut devices*
- Closed housing provides protection against paper dust
- Intake width: 400 mm
- Machine height: 990 mm
- Container volume: 146 litres
- Available in the following cutting versions:

5.8 mm strips, security level 2,

max. 67 sheets per cycle

3.9 mm strips, security level 2,

max. 50 sheets per cycle

3.9 x 50 mm particles, security level 3,

max. 40 sheets per cycle

1.9 x 15 mm particles, security level 4,

max. 28 sheets per cycle

0.78 x 11 mm particles, security level 5,

max. 19 sheets per cycle

1 x 5 mm particles, HS Level 6,

max. 10 sheets per cycle

* only with cutting version 3.9 x 50 mm and 1.9 x 15 mm

HSM 412.2 PROFESSIONAL

With its practical filling hopper, the HSM 412.2 is perfect for the frequent shredding of crumpled paper.



- · Touch-sensitive keypad for continuous and reverse operation
- Auto-stop when waste bag is full or door is open
- Automatic reverse for paper jams
- Convenient pull-out system with integrated reusable waste bag
- · Also shreds CDs, credit and store cards, floppy disks and DAT cartridges
- With infeed slot for floppy disks and CDs and splinter protection
- · Closed housing provides protection against paper dust
- Intake width: 400 mm
- Machine height: 1277 mm
- Container volume: 146 litres
- Available in the following cutting versions: 3.9 x 50 mm particles, security level 3, max. 40 sheets per cycle



crumpled paper







Cutting unit components of the



nuous and reverse operation



Automatic start / stop via light























HSM 450.2 PROFESSIONAL

max. 85 sheet

Regardless of whether individual sheets, entire computer lists, crumpled paper, credit and store cards, CDs or floppy disks are to be shredded – this power-pack can process all of your sensitive material even in very large quantities. And the intelligent filling hopper solution with rotary option allows the device to be filled even while it is operated.

- Large filling hopper for crumpled paper with rotary loading aid (security level 3 only)
- Touch-sensitive keypad for continuous and reverse operation
- Auto stop with LED to indicate whether the waste bag is full or the door is open
- Automatic reverse for paper jams
- Removable trolley to conveniently remove the sturdy reusable waste bag
- Practical storage space for paper stacks or lists
- Also shreds CDs and floppy disks (security level 3)
- Tried-and-tested, sturdy chain drive for maximum throughput
- With 3-phase power connection
- Mobile
- Intake width: 443 mm
- Machine height: 1590 mm (security level 3 with filling hopper)
- Machine height: 1460 mm (security level 4 without filling hopper)
- Container volume: 290 litres
- Available in the following cutting versions:
 3.9 x 50 mm particles, security level 3, max. 85 sheets per cycle
 - 2 x 15 mm particles, security level 4, max. 40 sheets per cycle



Filling hopper with rotary loa



Simultaneous infeed of norma and crumpled paper



Security Level 4 without filling



Reusable waste bag with



Touch-sensitive keypad and



Cutting unit components of the



Automatic start / stop via ligh





















HSM FA 400.2 PREMIUM

This HSM PREMIUM device is suited ideally for continuous operation at IT departments or in other business areas where

• Designed for large amounts and continuous

large amounts of paper have to be

 Material infeed via a conveyor belt – for optimum loading and maximum throughputs

Touch-sensitive keypad for continuous and

- Practical loading table for easy loading
- reverse operation
- Auto-stop with LED for full waste bag
- Automatic reverse for paper jams

shredded effectively.

- Convenient trolley with extremely sturdy reusable waste bag
- Practical storage space for paper stacks or
- Integrated manual oiler for cutting unit (particle cut devices only)
- Very sturdy gear motor with chain drive for maximum throughputs
- Extension of loading table available as accessory upon request
- Mobile
- Intake width: 428 mm
- Machine height: 1650 mm
- Collection volume: 460 litres resp. 2 x 230 litres – for easier handling
- Also available as combination systems with HSM baling press: SP 4040 V
- Available in the following cutting versions: 11.8 mm strips, security level 1, max. 180 sheets per cycle 5.8 mm strips, security level 2, max. 130 sheets per cycle 5.8 x 50 mm particles, security level 3, max. 120 sheets per cycle

HSM FA 490.1/500.2 PREMIUM

These two top models among the **HSM** document shredders are specialised on continuous operations at large departments and archives or as central shredding points.



- Material infeed via a conveyor belt for optimum loading and maximum throughputs
- Practical loading table for easy loading
- · Touch-sensitive keypad for continuous and reverse operation
- Automatic reverse for paper jams
- Integrated manual oiler for cutting unit (only with particle cut devices)
- · Very sturdy gear motor with chain drive for maximum throughputs
- Mobile
- Intake width: 500 mm
- Machine height FA 490.1: 1345 mm
- Machine height FA 500.2: 1410 mm
- Collection volume: 360 litres, optionally available with 2 x 180 litres (using a waste collection trolley with sturdy reusable waste bag as option)
- Also available as combination systems with HSM baling presses: SP 4940 V, SP 4980, SP 4988. SP 5080. SP 5088
- HSM FA 490.1 in the following cutting versions:
- 10.5 mm strips, security level 1, max. 250 sheets 5.8 mm strips, security level 2, max. 180 sheets 10.5 x 40-76 mm particles, security level 2, max. 440 sheets per cycle
- 7.5 x 40-80 mm particles, security level 2,
- max. 320 sheets per cycle
- 4.5 x 40-70 mm particles, security level 3, max. 220 sheets per cycle
- HSM FA 500.2 in the following cutting versions:
 - 10.5 x 40-76 mm particles, security level 2, max. 650 sheets per cycle
- 7.5 x 40-80 mm particles, security level 2,
- max. 550 sheets per cycle
- 6 x 40-53 mm particles, security level 3, max. 450 sheets per cycle



Loading table for easy



Cutting unit components of the highest quality



and additional main switch



FA 500.2 with waste collection trolley (figure similar



Reusable waste bag with trolley FA 400.2 (figure similar)
















HSM ProfiPack 400

Our powerful tabletop machine is portable and flexible in use and especially space-saving thanks to its compact size - it is the perfect solution for small dispatching and warehouse areas. It instantly transforms used cardboard into free packaging material, which can then disappear into the boxes waiting at the dispatch area.

- Thermal fuse protects the motor from overheating
- 230 V AC power connection
- Easy-to-operate rocker switch for ON/OFF and REVERSE
- Working width: 415 mm
- Infeed height: 10 mm
- Cutting capacity: 1 layer

HSM ProfiPack 425

This multi-functional cardboard shredder standing device has rollers for mobile operation. It can turn bulky old cardboard of delivered goods into multi-functional packaging material at practically no cost.



- The large motor ensures high throughput speeds and power reserves, which means it has no problems handling multiple layers
- Thermal fuses on all three phases protect the motor from overheating
- 3-phase power connection 3 x 400 V
- Rotary switch with the positions ON/OFF and REVERSE
- Working width: 425 mm
- Infeed height: 20 mm
- Cutting capacity: 2-3 layers



Compact table version



Easy-to-operate standing device



Specially developed cuttin and perforating rollers



Exact perforation and padding



Specially hardened HSM perforating rollers



The result: High-quality packaging material

HSM PROFIPACK – The technical features:

- Cutting <u>and</u> perforation in one cycle: time-consuming pre-cutting of cardboard no longer required
- The hardened cutting rollers, made from a single piece of metal, are completely resistant to damage from paper clips and other soft metal items
- The sturdy housing has been specially designed for the rigours of use at the dispatching area
- The practical measuring scale allows you to quickly measure the width of the material you require

HSM document shredders: The technical specifications at a glance

























| | | | | | | | |
 |
 |

 | ~ |
 |
 |
 | 4 | |
|-----------------|--|--|--|---|--|--|---
--

--
--
--

--

--
--|--|--|
| HSM 70.2 | HSM 80.2 | | HSM 90.2 | | HSM 102.2 | | HSM 104.3 |
 | HSM 105.3
 |

 | HSM 108.2 |
 | HSM 125.2
 |
 | HSM 225.2 | |
| strips | strips | particles | strips | particles | strips | particles | strips | particles
 | strips
 | particles

 | strips |
particles | strips
 | particles
 | strips | particles |
| 5.8 / 3.9 | 5.8 / 3.9 | 4 x 25 | 5.8 / 3.9 | 4 x 25 | 5.8 / 3.9 / 1.9 | 4 x 25 | 5.8 / 3.9 / 1.9 | 3.9 x 30 / 1.9 x 15
 | 5.8 / 3.9 / 1.9
 | 3.9x30 / 1.9x15 / 0.78x11

 | 5.8 / 3.9 | 3.9 x
30 / 1.9 x 15 | 5.8 / 3.9 / 1.9
 | 3.9x30 / 1.9x15 / 0.78x11 / 1x
 | x5 5.8 / 3.9 | 3.9x40 / 1.9x15 / 0.78x11 / 1x5 |
| 2 / 2 | 2 / 2 | 3 | 2 / 2 | 3 | 2/2/3 | 3 | 2/2/3 | 3 / 4
 | 2/2/3
 | 3 / 4 / 5

 | 2 / 2 | 3 / 4
 | 2/2/3
 | 3 / 4 / 5 / HS Level 6
 | 2 / 2 | 3 / 4 / 5 / HS Level 6 |
| ts 7 / 5 | 10-12 / 7-8 | 5 | 15 / 12 | 6 | 16-18 / 13-15 / 8-9 | 6-7 | 22-24 / 16-18 / 12-14 | 12-14 / 9-11
 | 22-24 / 16-18 / 12-14
 | 12-14 / 9-11 / 5-6

 | 22-24 / 16-18 | 12-14
/ 9-11 | 28-30 / 23-25 / 17-19
 | 16-18 / 12-14 / 7-8 / 4-5
 | 40-42 / 31-33 | 25-27 / 17-19 / 10-11 / 7-8 |
| ts 4-6 / 3-4 | 7-9 / 5-7 | 3-4 | 10-12 / 7-9 | 3-4 | 13-15 / 10-12 / 5-7 | 3-5 | 17-19 / 13-15 / 9-11 | 9-11 / 7-9
 | 17-19 / 13-15 / 9-11
 | 9-11 / 7-9 / 4-5

 | 17-19 / 13-15 | 9-11 /
7-9 | 22-24 / 18-20 / 13-15
 | 12-14 / 9-11 / 6-7 / 3-4
 | 32-33 / 25-27 | 20-22 / 12-14 / 7-9 / 6-7 |
| 80 | 80 | 80 | 60 | 60 | 60 | 60 | 80 | 90
 | 80
 | 90

 | 80 | 90
 | 120
 | 130
 | 126 | 135 |
| 225 | 225 | 225 | 225 | 225 | 225 | 225 | 240 | 240
 | 240
 | 240

 | 240 | 240
 | 255
 | 255
 | 300 | 300 |
| 80 W | 120 W | 120 W | 150 W | 150 W | 150 W | 150 W | 440 W | 440 W
 | 440 W
 | 440 W

 | 440 W | 440 W
 | 670 W
 | 670 W
 | 1400 W | 1400 W |
| 230 V/50 Hz | 230 V/50 Hz | 230 V/50 Hz | 230 V/50 Hz | 230 V/50 Hz | 230 V/50 Hz | 230 V/50 Hz | 230 V/50 Hz | 230 V/50 Hz
 | 230 V/50 Hz
 | 230 V/50 Hz

 | 230 V/50 Hz | 230
V/50 Hz | 230 V/50 Hz
 | 230 V/50 Hz
 | 230 V/50 Hz | 230 V/50 Hz |
| 297 x 180 x 384 | 305 x 200 x 410 | 305 x 200 x 410 | 326 x 240 x 423 | 326 x 240 x 423 | 365 x 273 x 500 | 365 x 273 x 500 | 375 x 281 x 583 | 375 x 281 x 583
 | 375 x 281 x 583
 | 375 x 281 x 583

 | 401 x 272 x 727 | 401 x
272 x 727 | 448 x 347 x 828
 | 448 x 347 x 828
 | 500 x 420 x 895 | 500 x 420 x 895 |
| 1.8 | 3.8 | 3.8 | 4 | 4.5 | 6.3 | 6.8 | 11.5 | 12.5
 | 11.5
 | 12.5

 | 19 | 20
 | 26
 | 30
 | 42 | 45 - 48 |
| l 14 | 17 | 17 | 25 | 25 | 25 | 25 | 33 | 33
 | 33
 | 33

 | 48 | 48
 | 76
 | 76
 | 105 | 105 |
| t | strips 5.8 / 3.9 2 / 2 s 7 / 5 s 4-6 / 3-4 80 225 80 W 230 V/50 Hz 297 x 180 x 384 1.8 | strips strips 5.8 / 3.9 5.8 / 3.9 2 / 2 2 / 2 s 7 / 5 10-12 / 7-8 s 4-6 / 3-4 7-9 / 5-7 80 80 225 225 80 W 120 W 230 V/50 Hz 230 V/50 Hz 297 x 180 x 384 305 x 200 x 410 1.8 3.8 | strips strips particles 5.8 / 3.9 5.8 / 3.9 4 x 25 2 / 2 2 / 2 3 s 7 / 5 10-12 / 7-8 5 s 4-6 / 3-4 7-9 / 5-7 3-4 80 80 80 225 225 225 80 W 120 W 120 W 230 V/50 Hz 230 V/50 Hz 230 V/50 Hz 297 x 180 x 384 305 x 200 x 410 305 x 200 x 410 1.8 3.8 3.8 | strips strips particles strips 5.8 / 3.9 5.8 / 3.9 4 x 25 5.8 / 3.9 2 / 2 3 2 / 2 5 7 / 5 10-12 / 7-8 5 15 / 12 5 4-6 / 3-4 7-9 / 5-7 3-4 10-12 / 7-9 80 80 60 225 225 225 80 W 120 W 120 W 150 W 230 V/50 Hz 230 V/50 Hz 230 V/50 Hz 230 V/50 Hz 297 x 180 x 384 305 x 200 x 410 305 x 200 x 410 326 x 240 x 423 1.8 3.8 3.8 4 | strips strips particles strips particles 5.8 / 3.9 5.8 / 3.9 4 x 25 5.8 / 3.9 4 x 25 2 / 2 2 / 2 3 2 / 2 3 s 7 / 5 10-12 / 7-8 5 15 / 12 6 s 4-6 / 3-4 7-9 / 5-7 3-4 10-12 / 7-9 3-4 80 80 80 60 60 225 225 225 225 225 80 W 120 W 120 W 150 W 150 W 230 V/50 Hz 297 x 180 x 384 305 x 200 x 410 305 x 200 x 410 326 x 240 x 423 326 x 240 x 423 1.8 3.8 3.8 4 4.5 | strips strips particles strips particles strips 5.8 / 3.9 5.8 / 3.9 4 x 25 5.8 / 3.9 4 x 25 5.8 / 3.9 / 1.9 2 / 2 2 / 2 3 2 / 2 3 2 / 2 / 3 5 7 / 5 10-12 / 7-8 5 15 / 12 6 16-18 / 13-15 / 8-9 5 4-6 / 3-4 7-9 / 5-7 3-4 10-12 / 7-9 3-4 13-15 / 10-12 / 5-7 80 80 80 60 60 60 225 225 225 225 225 225 80 W 120 W 120 W 150 W 150 W 150 W 230 V/50 Hz 297 x 180 x 384 305 x 200 x 410 305 x 200 x 410 326 x 240 x 423 326 x 240 x 423 365 x 273 x 500 1.8 3.8 4 4.5 6.3 | strips strips particles strips particles strips particles 5.8/3.9 5.8/3.9 4 x 25 5.8/3.9 4 x 25 5.8/3.9/1.9 4 x 25 2/2 2/2 3 2/2/3 3 2/2/3 3 8 7/5 10-12/7-8 5 15/12 6 16-18/13-15/8-9 6-7 8 4-6/3-4 7-9/5-7 3-4 10-12/7-9 3-4 13-15/10-12/5-7 3-5 80 80 80 60 60 60 60 225 225 225 225 225 225 225 80 W 120 W 120 W 150 W 150 W 150 W 150 W 230 V/50 Hz 68 x 273 x 500 365 x 273 x 500 4.5 | strips strips particles strips <td>strips strips particles strips particles strips particles 5.8/3.9 5.8/3.9 4 x 25 5.8/3.9 4 x 25 5.8/3.9/1.9 4 x 25 5.8/3.9/1.9 3.9 x 30/1.9 x 15 2/2 2/2 3 2/2 3 2/2/3 3 2/2/3 3/4 8/7/5 10-12/7-8 5 15/12 6 16-18/13-15/8-9 6-7 22-24/16-18/12-14 12-14/9-11 8/4-6/3-4 7-9/5-7 3-4 10-12/7-9 3-4 13-15/10-12/5-7 3-5 17-19/13-15/9-11 9-11/7-9 8/0 8/0 8/0 6/0 6/0 6/0 8/0 9/0 225 225 225 225 225 225 225 24/0 24/0 8/0 W 120 W 120 W 150 W 150 W 150 W 440 W 230 V/50 Hz 230 V/50 Hz<!--</td--><td>strips strips particles strips<td>strips strips particles strips<td>strips strips particles strips<td>strips strips particles strips<td>strips strips particles strips<td>strips strips particles strips particles</td><td>strips strips particles strips particles</td></td></td></td></td></td></td> | strips strips particles strips particles strips particles 5.8/3.9 5.8/3.9 4 x 25 5.8/3.9 4 x 25 5.8/3.9/1.9 4 x 25 5.8/3.9/1.9 3.9 x 30/1.9 x 15 2/2 2/2 3 2/2 3 2/2/3 3 2/2/3 3/4 8/7/5 10-12/7-8 5 15/12 6 16-18/13-15/8-9 6-7 22-24/16-18/12-14 12-14/9-11 8/4-6/3-4 7-9/5-7 3-4 10-12/7-9 3-4 13-15/10-12/5-7 3-5 17-19/13-15/9-11 9-11/7-9 8/0 8/0 8/0 6/0 6/0 6/0 8/0 9/0 225 225 225 225 225 225 225 24/0 24/0 8/0 W 120 W 120 W 150 W 150 W 150 W 440 W 230 V/50 Hz 230 V/50 Hz </td <td>strips strips particles strips<td>strips strips particles strips<td>strips strips particles strips<td>strips strips particles strips<td>strips strips particles strips<td>strips strips particles strips particles</td><td>strips strips particles strips particles</td></td></td></td></td></td> | strips strips particles strips <td>strips strips particles strips<td>strips strips particles strips<td>strips strips particles strips<td>strips strips particles strips<td>strips strips particles strips particles</td><td>strips strips particles strips particles</td></td></td></td></td> | strips strips particles strips <td>strips strips particles strips<td>strips strips particles strips<td>strips strips particles strips<td>strips strips particles strips particles</td><td>strips strips particles strips particles</td></td></td></td> | strips strips particles strips <td>strips strips particles strips<td>strips strips particles strips<td>strips strips particles strips particles</td><td>strips strips particles strips particles</td></td></td> | strips strips particles strips <td>strips strips particles strips<td>strips strips particles strips particles</td><td>strips strips particles strips particles</td></td> | strips strips particles strips <td>strips strips particles strips particles</td> <td>strips strips particles strips particles</td> | strips strips particles | strips strips particles |

















8







MODEL	HSM 386.2		HSM 390.3		HSM 411.2		HSM 412.2	HSM 450.2	HSM FA 400.2		HSM FA 490.1		HSM FA 500.2	HSM ProfiPack	400	425
Cutting type	strips	particles	strips	particles	strips	particles	particles	particles	strips	particles	strips	particles	particles	Working width in mm	415	425
Cutting size in mm	3.9	3.9 x 30 / 1.9 x 15	5.8 / 3.9	3.9x40 / 1.9x15 / 0.78x11 / 1x5	5.8 / 3.9	3.9x50 / 1.9x15 / 0.78x11 / 1x5	3.9 x 50	3.9 x 50 / 2 x 15	11.8 / 5.8	5.8 x 50	10.5 / 5.8	10.5x40-76/7.5x40-80/4.5x40-7L	0 10.5 x 40-76 / 7.5 x 40-80 / 6 x 40-53	Infeed height in mm	10	20
Security level DIN 32757-1*	2	3 / 4	2 / 2	3 / 4 / 5 / HS Level 6	2 / 2	3 / 4 / 5 / HS Level 6	3	3 / 4	1 / 2	3	1 / 2	2/2/3	2/2/3	Cutting capacity in layers	1	2-3
Cutting capacity**70g/m²in sheets	s 23-25	16-18 / 12-14	40-42 / 31-33	25-27 / 17-19 / 10-11 / 7-8	65-67 / 48-50	38-40 / 26-28 / 17-19 / 9-10	38-40	80-85 / 35-40	180 / 130	120	230-250 / 160-180	420-440/300-320/200-220	600-650 / 500-550 / 400-450			
Cutting capacity**80g/m² in sheets		12-14 / 9-11	33-35 / 25-27	20-22 / 13-15 / 7-9 / 6-7	51-53 / 38-40	33-35 / 20-22 / 12-14 / 7-8	33-35	65-70 / 28-32	144 / 104	96	180-200 / 120-140	330-350/240-260/160-180	510-550 / 425-470 / 340-380	Cutting speed in m/min	8	12
	120	135 / 130	126	135	100	110	110	218	210	220	235	250	210	Motor in kW	1.15	4
	386	386	400	400	400	400	400	443	428	428	500	500	500	Voltage / Frequency	230 V/50 Hz	3 x 400 V/50 Hz
Motor	670 W	670 W	1400 W	1400 W	2100 W	2100 W	2100 W	3 kW / 2,2 kW	4 kW	4 kW	2 x 3 kW	2 x 3 kW	9.2 kW	Dimensions W x D x H in mm	n 590 x 370 x 3	360 700 x 480 x 970
Voltage / Frequency	230 V/50 Hz	230 V/50 Hz	230 V/50 Hz	230 V/50 Hz	230 V/50 Hz	230 V/50 Hz	230 V/50 Hz	3 x 400 V/50 Hz	3 x 400 V/50 Hz	3 x 400 V/50 Hz	3 x 400 V / 50 Hz	3 x 400 V / 50 Hz	3 x 400 V/50 Hz	Weight in kg	37.2	175
	548 x 412 x 860	548 x 412 x 860	595 x 510 x 915	595 x 510 x 915	595 x 470 x 990	595 x 470 x 990	595 x 470 x 1277	750 x 665 x 1590/1460	1157 x 1568 x 1650	1157 x 1568 x 1650	1160x1700x1345	1160x1700x1345	1155 x 2510 x 1410			
Weight in kg	33	35	48	56-58	74	82	87	220	425	425	600	600	725			
Container/collection volume in l	I 116	116	148	148	146	146	146	290	460 resp. 2 x 230	460 resp. 2 x 230						

*HS Level 6 is still out of DIN standard 32757-1. **max. per cycle DIN A4, 70 g/m² resp. DIN A4 80 g/m². All technical specifications are approximate values. Technical and design modifications reserved.













The suitability of the different materials depends on the respective cutting size of the models. See product descriptions for details.

Security levels at a glance



SECURITY LEVEL 1

For general documents that is to be rendered illegible after expiry



SECURITY LEVEL 2

For internal documents that need to be rendered illegible such as computer lists or bad copies



SECURITY LEVEL 3

For confidential documents e.g. personal data and documents



SECURITY LEVEL 4

When the confidentiality of documents is of existence importance for the company



SECURITY LEVEL 5

For secret documents where extraordinary security requirements must be adhered to, such as government offices or fundamental research



HS Level 6

This is the maximum security feature developed by HSM (out of DIN standard) - especially for shredding highly confidential documents

This is how we calculate the technical data

The technical data and dimensions of the document shredders in detail:

Cutting type:	The strips or particles resulting from shredding the material.
Cutting size:	Dimension of the strips or particles of the shredded material (depending on the paper quality).
Security levels:	In accordance with DIN 32757-1, except HS Level 6, developed by HSM.
Cutting capacity:	The max. number of sheets (DIN A 4, 70 g/m² or 80 g/m²), fed lengthwise, with cold motor and lubricated cutting unit,
	which can be cut in one cycle.
Cutting speed:	This is calculated on the basis of the external diameter and speed of the cutting rollers in idle operation.
Intake width:	Maximum effective width of the intake opening.
Motor:	Power consumption of motor at maximum cutting capacity (see above).
Voltage / frequency:	Three-phase/alternating current power supply.
Dimensions:	External dimensions of the machine when ready for operation.
Weight:	Net weight of machine without packaging.
Container volume / collecting container :	Total volume of the collecting container resp. collection capacity for shredded material until the machine switches off.

The technical data and dimensions of the cardboard shredders in detail:

Working width:	Maximum effective width of the feed opening.
Infeed height:	Height of the intake opening.
Cutting capacity:	The number of layers of cardboard which can be cut in one cycle.
Cutting speed:	This is calculated on the basis of the external diameter and speed of the cutting rollers in idle operation.
Motor:	Power consumption of the motor at maximum cutting capacity (see above).
Voltage / frequency:	Three-phase/alternating current power supply.
Dimensions:	External dimensions of the machine when set up for operation.
Weight:	Net weight of machine without packaging.



Deutschland / Germany:

HSM GmbH + Co. KG Bahnhofstrasse 115 88682 Salem

Vertrieb / Sales: Werk Frickingen Austrasse 1 88699 Frickingen

Tel. +49 (0) 75 53 / 822-0 Fax +49 (0) 75 53 / 822-160 info@hsm-online.de

International:

HSM GmbH + Co. KG Adresse postale: 1 rue de la Haye Le Dôme - BP 12910 95731 ROISSY CDG CEDEX Adresse salle d'exposition: Paris Nord II 33 rue des Chardonnerets 95971 ROISSY Tel. N°Azur 0810.12.26.33 PRIX APPEL LOCAL Fax N°Indigo 0820.20.84.80 0,118 EURO TTC / MN HSM.France@hsm-online.de

HSM GmbH + Co. KG Oficina Barcelona Plaça dels Nostres Avis, 3 08450 Llinars del Vallès BARCELONA Tel. +34 93.84.10.760 Fax +34 93.84.10.631 HSM.Spain@hsm-online.de HSM Verkoop Nederland Tel. 0800 0203740 Fax 0800 0203739 HSM.Benelux@hsm-online.de

HSM Verkoop België + Luxemburg Tel. +49 (0) 75 53 / 822-354/271 Fax +49 (0) 75 53 / 822-260 HSM.Benelux@hsm-online.de

HSM Vertrieb Österreich Tel. +49 (0) 75 53 / 822-222 Fax +49 (0) 75 53 / 822-272 HSM.Austria@hsm-online.de 1075 Andrew Drive, Suite C West Chester PA 19380 Tel. (610) 918-4894 (800) 613-2110 Fax (610) 918-4899 customerservice@hsmofamerica.com info@hsmofamerica.com www.hsmofamerica.com

HSM (UK) Ltd.
14 Attwood Road / Zone 1
Burntwood Business Park
Burntwood
Staffordshire
WS7 3GJ
Tel. +44 (0) 1543.272.480
Fax +44 (0) 1543.272.080
info@hsmuk.co.uk
www.hsmuk.co.uk

HSM of America LLC

www.hsm-online.de

Ihr HSM-Partner / Your HSM partner

