

TCP-650

Fanless All-in-One POS Terminal

Slim and Powerful

15" all-in-one POS terminal with ultra-slim enclosure and power efficient Intel Bay Trail Quad-Core processor



- Low-power consumption CPU, reliability and flexibility POS Terminal
- Easy access to hard driver disk for improving maintenance and service speed
- Various peripherals - VFD, Second Display and MSR

TCP-650

Specification

CPU	Intel Celeron J1900 (2.0 GHz) quad-core processor
Memory	1 x 4GB DDR3L 1333 (Max. 8GB)
Storage	128GB SSD
Color	16.2M/ 262K Colors
LCD Display Size	15" TFT LCD
Touch	Taiwan 5 Wire Resistive Touch
Brightness	350cd/m2
Resolution	1024 x 768

I/O Ports

USB 3.0	1
USB 2.0	3
Cash Drawer Port	1 (RJ11 12V/ 24V)
Serial Port	4 (RJ45 with DC 5V/12V selectable)
Audio Port	1
VGA Port	1
LAN Port	1 (RJ45 10/100/1000 M)
I/O Port Option	Type A: USB 2.0 X 2, UPS connector X 1, Line-out X 1 Type B: RJ45 with DC 5V/12V selectable X 1, UPS connector X 1, Line-out X 1 Type C: USB 2.0 X 2 , 24V Powered USB X 1, Mic X 1, Line-out X 1 Type D: Standard Parallel X 1

Peripheral

MSR	JIS-I or II, ISO Track 1/2/3 USB (Build-in USB Interface)
Second Display	8" / 10.4" without touch
Customer Display	VFD display 2 x 20 characters

Environment

Operating Temperature	0°C ~ 35°C
Storage Temperature	-0°C ~ 60°C

Electrical

Power Supply	60W / 90W / 150W 19V power adapter
--------------	------------------------------------

Physical

Chassis Housing Color	Aluminium / Black
Dimension	323.6mm (W) x 264.2mm (H) x 368mm (D)

[Notice] : Specification are subject to change without notice