

TCP-9015N

Fanless All-in-One POS Terminal

Slim and Powerful

The sleek and elegant design of TCP-9015N makes it a perfect fit to the retail and hospitality industry. With Intel's Bay Trail, the fanless TCP-9015N guarantees outstanding performance and enhances customer experience. Seamless integration of numerous peripheral modules such as MSR, iButton, Fingerprint, Second Display and Customer Display.



- ✓ Slim and Robust
- ✓ Intelligent Cable Management



- ✓ Fan-less and Silent
- ✓ Tool-less Design
- ✓ VFD and Second Display



- ✓ Peripheral with Blade Connectivity

TCP-9015N

Specification	D36	D86U
CPU	Intel Bay Trail Celeron J1900 2.4 GHz	Intel Skylake U i3-6100U 2.3 GHz Intel Skylake U i5-6200U 2.3 GHz
Memory	1 x 4GB DDR3L SO-DIMM up to 8GB	
Storage	1x 2.5" 500GB SATA HDD or 128GB SSD	
Touch	True Flat PCAP Touch	
Display	15" LED	
Resolution	1024 x 768	
Brightness	300 nits	350 nits
I/O Ports		
USB 3.0	1	4
USB 2.0	4	2
Cash Drawer Port	1 (RJ11 12V/ 24V)	
Serial Port	3 (RJ45 with DC 5V/12V selectable)	
Audio Port	1	
VGA Port	1	
LAN Port	1 (RJ45)	
Optional I/O Port	1 x 12V, 1 x 24V (Powered USB)	
Optional Peripheral		
MSR	ISO Track 1/2/3 (USB)	
Second Display	8.4" / 10.1" without touch	
Customer Display	LCM display 2 x 20 characters (USB)	
Security	iButton / Fingerprint Reader (USB)	
Wifi Kit	802.11 b/g/n WLAN card & Antenna	
Second Storage (D86U Only)	128GB module type SSD with bracket (No raid function)	
Environment		
Operating Temperature	0°C ~ 35°C	
Storage Temperature	-20°C ~ 60°C	
Humidity	20% ~ 80% RH non-condensing	
Certificate		
EMC & Safety	FCC Class A, CE Mark, LVD	
Electrical		
Power Supply	65W / 19V (120W /19V with PUSB 12V & 24V)	
Physical		
Dimension	360mm (W) x 210mm (D) x 316mm (H)	
Weight	4.5kg	
Mounting	VESA Mount 100 x 100	
Operating System	Windows 7, POSReady 7, Windows Embedded 8.1 Industry, Windows 10 IoT Enterprise	

[Notice] : Specification are subject to change without notice

