

The AMOUR Series is designed especially for cash deposites after office hours or any time of the day. The slot drawer at the top section of the safe enables easy drop-in deposit with practical & heavy duty feature.

The AMOUR Series comes in a variation of the slot drawer facing front or facing back.\*


Body : Made of high density proofing material encased in steel to resist attacks such as fire, drilling, oxyacetylene or mechanical tools attack

**Boltwork**: The handle controls the one way movable bolts that keeps the door firmly shut and locked. Behind the hinges, a 75mm thick (or 102mm for Model BKT1) vertical interlocking rebate is integrated to withstand prying attack.

Door : The interior of the door is further armoured with high density proofing material while securing the lockcase embedded in the door structure.

Locking : Standard locking system with three wheel combination lock, capable of providing 1,000,000 combinations plus seven lever keylocks. Deadlock device system is incorporated to jam on the boltwork mechanism if forcible attacks are made on the door and locks.

\*applicable for Model TS 3 only.



Model	Locks	Dimension (H x W x D)		Net Weight		Locks Dimension					
		external	internal	+/- kg	+/- lbs	a	b	C	d	0	f
TS1	KCL / KL & KCL	516 x 512 x 465	248 x 369 x 287	180	396	50	210	75	150	50	75
TS2	KL & KCL	789 x 480 x 517	427 x 338 x 362	280	616	50	210	75	150	50	75
TS3	KL & KCL	1024x 618 x 660	706 x 445 x 457	700	1540	65	210	75	150	65	75
BKT 1	KL & KCL	854 x 610 x 660	512 x 378 x 416	620	1364	65	210	75	150	65	75

REMARK: KL = KEY LOCK

KCL = KEYLESS COMBINATION LOCK



**Authorized Dealer** 

C

e