



PRODUCT SPECIFICATIONS					
External Size (HxWxD)			Internal Size (HxWxD)		
553	508	533	255	368	381
mm	mm	mm	mm	mm	mm
Drawer Size (HxWxD)					
110	310	300			
mm	mm	mm			
Fire Resistant			Weight		
1 Hour (1000° Celcius)			210 kg		




PRODUCT SPECIFICATIONS					
External Size (HxWxD)			Internal Size (HxWxD)		
756	508	533	368	368	381
mm	mm	mm	mm	mm	mm
Drawer Size (HxWxD)					
110	310	300			
mm	mm	mm			
Fire Resistant			Weight		
1 Hour (1000° Celcius)			320 kg		




PRODUCT SPECIFICATIONS					
External Size (HxWxD)			Internal Size (HxWxD)		
*refer to AEGIS S1, S2, S3 standard size.			*refer to AEGIS S1, S2, S3 standard size.		
Slot Hole (WxD)			Weight		
115	10		*refer to AEGIS S1, S2, S3 standard weight.		
mm	mm				

YOUR ULTIMATE PREMIUM SAFE - AEGIS S-SERIES

AEGIS S-Series is built with a convenient size that are able to fit in most of the allocated place. It is suitable for home, condominium, office and small retail businesses to store important documents. This product also provides drawer as a security enhancement option.



75mm Body
Body Thickness



50mm Door
Door Thickness



High Security Lock
(Combination, Digital & Key)
with Live Relocking System



1 Hour
Fire Resistant
Anti-Burglary



Local Manufactured
Proudly made in
Malaysia

AEGEUS
SAFE & VAULT MANUFACTURER

40 Years
Taylormade
Safe Experience

Product
Catalogue
02

AEGIS S-SERIES
PREMIUM SAFE





PRODUCT SPECIFICATIONS					
External Size (HxWxD)			Internal Size (HxWxD)		
395	508	533	255	368	381
mm	mm	mm	mm	mm	mm

Locking System
1 Unit x 3 wheel combination lock with 1,000,000 possible combinations
1 Unit x Cylinder Lock

Locking Protection
4 Units x 25mm moving solid steel bolts

Fire Resistant	Weight
1 Hour (1000° Celcius)	165 kg



PRODUCT SPECIFICATIONS					
External Size (HxWxD)			Internal Size (HxWxD)		
508	458	533	368	317	381
mm	mm	mm	mm	mm	mm

Locking System
1 Unit x 3 wheel combination lock with 1,000,000 possible combinations
1 Unit x Cylinder Lock

Locking Protection
4 Units x 25mm moving solid steel bolts

Fire Resistant	Weight
1 Hour (1000° Celcius)	190 kg



PRODUCT SPECIFICATIONS					
External Size (HxWxD)			Internal Size (HxWxD)		
600	508	533	457	368	381
mm	mm	mm	mm	mm	mm

Locking System
1 Unit x 3 wheel combination lock with 1,000,000 possible combinations
1 Unit x Cylinder Lock

Locking Protection
4 Units x 25mm moving solid steel bolts

Fire Resistant	Weight
1 Hour (1000° Celcius)	280 kg



PRODUCT SPECIFICATIONS					
External Size (HxWxD)			Internal Size (HxWxD)		
760	508	533	622	368	381
mm	mm	mm	mm	mm	mm

Locking System
1 Unit x 3 wheel combination lock with 1,000,000 possible combinations
1 Unit x Mauer Lock (KABA)

Locking Protection
5 Units x 25mm moving solid steel bolts

Fire Resistant	Weight
1 Hour (1000° Celcius)	350 kg



PRODUCT SPECIFICATIONS					
External Size (HxWxD)			Internal Size (HxWxD)		
1045	660	625	905	520	405
mm	mm	mm	mm	mm	mm

Locking System
1 Unit x 3 wheel combination lock with 1,000,000 possible combinations
1 Unit x Mauer Lock (KABA)

Locking Protection
6 Units x 25mm moving solid steel bolts

Fire Resistant	Weight
1 Hour (1000° Celcius)	480 kg



PRODUCT SPECIFICATIONS					
External Size (HxWxD)			Internal Size (HxWxD)		
1330	660	625	1190	520	405
mm	mm	mm	mm	mm	mm

Locking System
1 Unit x 3 wheel combination lock with 1,000,000 possible combinations
1 Unit x Mauer Lock (KABA)

Locking Protection
8 Units x 25mm moving solid steel bolts

Fire Resistant	Weight
1 Hour (1000° Celcius)	680 kg